

Product Safety Data Sheet	Document No.	
	Issue	01.00
	Date Last Amended	August 2017
	Last Amended by	JN
Document Title	LB4V Lithium Battery Module PSDS	

Product Name: Lithium Battery Module Type №: 1061

For use with: ACR SR203 GMDSS VHF handheld radio

Chemistry: LiFeS<sub>2</sub> Total Weight: 148g Nominal Voltage: 3V

**Construction:** Battery module containing three isolated batteries, each of two

Duracell LF1500 cells connected in series

**Lithium weight/cell:** ~0.98g **Total lithium weight/battery:** 1.96g

**Section 1 - Manufacturer Information** 

Manufactured by: Ocean Signal Ltd., Unit 4, Ocivan Way, Margate, Kent, CT9

4NN, United Kingdom

EMERGENCY 24-HOUR TELEPHONE NUMBERS: CHEM-TEL, INC, Inside U.S. (800) 255-3924, Outside U.S. (813) 248-0585 and FAX (813) 248-0582 see www.chemtelinc.com for more information about Chem-Tel, Inc.

## **Section 2 - Hazards Identification**

This battery module is a sealed unit. In this condition there are no hazards identified. Should the battery be damaged to cause leakage of the cell contents, the following hazards should be noted.

**Ingestion:** Swallowing the contents of a damaged battery can be harmful **Inhalation:** Contents of a damaged battery can cause respiratory irritation

**Skin Contact:** Contents of a damaged battery can cause irritation

**Eye Contact:** Contents of a damaged battery can cause severe irritation

## **Section 3 - Ingredients**

Important Note: This battery module should not be opened or burned. Exposure to the contents may be harmful.

Material or Ingredient	PEL (OSHA)	TLV (ACGIH)	%/wt.
Lithium (CAS# 7439-93-2)	None Established	None established	<5%
Iron Disulfide (CAS# 1309-36-0)	None Established	None Established	<23%
1,3-Dioxolane (CAS# 646-06-0)	None Established	None Established	<5.5%
Lithium bis- Trifluoromethanesulfonimide (CAS# 90076-65-6)	None Established	None Established	<5.5%
Tetramethahylene Sulfolane (CAS# 126-33-0)	None Established	None Established	<1.5%
Non Hazardous Components			
Steel (CAS#7439-89-6)	None Established	None Established	<20%
Plastic and other	None Established	None Established	Remainder

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.

Product Safety Data Sheet	Document No.	
	Issue	01.00
	Date Last Amended	August 2017
	Last Amended by	JN
Document Title	LB4V Lithium Battery Module PSDS	

## **Section 4 – First Aid Measures**

The following advice applies only to damaged battery packs that are leaking.

**Ingestion:** Seek medical advice. Do not induce vomiting or give food or drink.

**Inhalation:** Seek medical attention. Provide fresh air

Skin Contact: Remove any contaminated clothing and wash affected areas with soap

and water.

Eye Contact: Seek medical attention. Immediately flush eyes with water for a

minimum of 15minutes. Ensure that both upper and lower eyelids are

lifted during the flushing process.

# **Section 5 – Fire Fighting Measures**

In case of fire involving lithium batteries, flood the area with water or smother with a class D fire extinguishing material suitable for lithium metal. (e.g. Lith-X)

Note: Water may not completely extinguish burning lithium batteries but will keep adjacent batteries cool reducing the risk of the fire spreading. As burning batteries will burn themselves out, flooding with water will control virtually all fires involving lithium batteries. However, the contents of lithium batteries will react with water to release hydrogen gas. In enclosed spaces this can cause an explosive mixture. Use a smothering agent in enclosed spaces which will extinguish burning lithium batteries.

Fire responders should wear self contained breathing apparatus.

## **Section 6 - Accidental Release Measures**

Should batteries leak the following actions are recommended.

**Ventilation:** Keep room containing leaking lithium batteries well ventilated

**Respiratory Protection:** Avoid exposure to fumes from open or leaking batteries

**Eye protection:** Wear safety glasses with side shields when handling leaking

batteries

Gloves: Neoprene of natural rubber gloves should be worn when

handling leaking batteries

**Storage:** Leaking batteries should be stored in a leak proof container

## Section 7 – Handling and Storage

**Storage:** Store in a cool, well ventilated area. Elevated temperature may result

in shortened battery life.

**Handling:** Avoid accidentally short circuiting batteries. Prolonged short circuiting

cause the battery temperature to rise and significantly reduce battery

life.

**Charging:** These batteries are not designed for charging. Do not attempt to

recharge the battery. Recharging may result in cell venting or rupture.

## Section 8 - Exposure Controls / Personal Protection

No special requirements are required for this battery under normal circumstances.

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.

Product Safety Data Sheet	Document No.	
	Issue	01.00
	Date Last Amended	August 2017
	Last Amended by	JN
Document Title	LB4V Lithium Battery Module PSDS	

Section 9 -	Physical	and Chemical	<b>Properties</b>
-------------	----------	--------------	-------------------

Boiling Point at 760mm Hg (°C)	Not applicable for this item
Vapour Pressure (mm Hg at 25°C)	Not applicable for this item
Vapour Density	Not applicable for this item
Density (g/cm³)	
Percent volatile by volume (%)	Not applicable for this item
Evaporation Rate	Not applicable for this item
Physical State	Solid
Solubility in water	Not applicable for this item
рН	Not applicable for this item
Appearance and odour	Solid object / no odour

# Section 10 - Stability and Reactivity

No stability or reactivity issues identified

## Section 11 – Toxicological Information

This battery module is not classified as hazardous waste. This battery module has been manufactured in accordance with the EU ROHS directive, 2002-95-EC.

## **Section 12 – Ecological Information**

No ecological issues have been identified for this battery

## **Section 13 – Disposal Considerations**

Dispose of battery module in accordance with applicable local regulations

## Section 14 – Transport Information

This battery module has been tested in accordance with subsection 38.3 of part III of the UN Manual of Tests and Criteria.

This battery module (classification UN3090) should be transported by air in accordance with the IATA dangerous goods regulations. When supplied with equipment (classification UN3091) it should be packed in accordance with packing instruction 969 section 2.

The battery modules may be transported by road under special provision 188 of the ADR.

## **Section 15 Regulatory Information**

No additional regulatory requirements are identified for this battery module.

## Section 16 - Other

No information

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.