



# ACR Firefly®

Firefly®<sub>3</sub> and Firefly®<sub>3</sub> Waterbug™



## STROBE LIGHTS



THE SCIENCE OF SURVIVAL



Scan With Phone  
[www.ACRARTEX.com](http://www.ACRARTEX.com)



# ACR Firefly<sup>®</sup>



## Firefly<sup>®</sup><sub>3</sub>

Manually Activated Rescue Strobe

The Firefly<sub>3</sub> is the state-of-the-art heir to its famous forerunners, the Firefly4F and 4G. Using a high-intensity omni-directional Xenon 360° strobe, it cuts through the foulest conditions with a state-of-the-art lamp/lens combo that creates a super-bright flash visible from beyond 1 nm (1.9 km). The Firefly<sub>3</sub> surpasses SOLAS specifications.

## Firefly<sup>®</sup><sub>3</sub> Waterbug™

Water-Activated Rescue Strobe

With its special water-activation feature, this powerful rescue strobe automatically turns on when armed and in contact with water. Like the standard Firefly<sub>3</sub> model, the Waterbug™ delivers 250,000 peak lumens in a 360° beam, offering maximum rescue visibility. Visible from beyond 1 nm (1.9 km).

## SPECIFICATIONS

	Firefly <sup>®</sup> <sub>3</sub>	Firefly <sup>®</sup> <sub>3</sub> Waterbug™
Product Number	3995.4 bulk 3995.3 carded	3996.4 bulk 3996.3 carded
Size	4.7 x 2.2 x 1.2 in (12.0 x 5.7 x 2.8 cm)	4.7 x 2.2 x 1.2 in (12.0 x 5.7 x 2.8 cm)
Weight	3.7 oz. (106 g) with 2 AA lithium batteries (Batteries not included)	3.8 oz. (108.7 g) with 2 AA lithium batteries (Batteries not included)
Operation	Manual ON/OFF switch	Manual ARM/OFF switch Immerse in water to activate when switch is armed
Waterproof	Factory tested to 33 ft. (10 m)	Factory tested to 33 ft. (10 m)
Lamp	High intensity xenon strobe	High intensity xenon strobe
Strobe Intensity	.75 cd minimum	.75 cd minimum
Strobe Visibility	1-2 mi (1.6 to 3.2 km)	1-2 mi (1.6 to 3.2 km)
Strobe Flash Rate	60± 10/min.	60± 10/min.
Strobe Operation	Minimum 18 hr. continuous @ 30°F (-1°C)	Minimum 18 hr. continuous @ 30°F (-1°C)
Certification	SOLAS (with lithium batteries), USCG, IMO LSA, FAA TSO-C85b, MED approved	SOLAS (with lithium batteries), USCG, IMO LSA, FAA TSO-C85b, MED approved
Limited Warranty	1 year	1 year
ARM Mode Storage	N/A	13 Months (Lithium L91 Energizer Batteries)



For further information please contact:

**ACR Electronics, Inc.**  
5757 Ravenswood Road  
Fort Lauderdale, FL 33312

Tel: (954) 981.3333  
Fax: (954) 983.5087  
Email: sales@acrartex.com