

ACR EPIRB Accessories

For 406 MHz Beacons

The Science of Survival



COBHAM



ACR EPIRB Accessories

For 406 MHz Beacons



Sea Shelter™₃ Category I Bracket

This fully enclosed, robust bracket provides EPIRB protection in the harshest conditions, and automatically deploys your EPIRB should your vessel sink. The quick-release latch allows for fast, easy top cover removal, even with gloves on. Ideal for use in fishing, petro-chemical, freighter, salvage or any other harsh marine applications. The Sea Shelter™₃ also features a streamlined, aesthetic design perfect for yachts or racing vessels.

- // Innovative, quick-change hydrostatic release mechanism
- // One-way mounting eliminates the possibility of installing EPIRB backwards
- // Integral de-activation magnet prevents the EPIRB from transmitting until deployed
- // Deploys EPIRB when submerged in water at a depth between 4.9 – 13.1 ft (1.5 – 4 m)

Product Number	9501
Fits	GlobalFix™ iPRO (P/N 2846.0), GlobalFix™ PRO (P/N 2842)
Size	14.3 x 5.9 x 4.7" (36.5 x 15.0 x 12.0 cm)
Weight	2.23 lbs (1.01 kg)

Sea Shelter™₂ Category I Bracket

Automatic Category I Sea Shelter™₂ bracket is fully enclosed and is made of high-density, UV-stabilized polyethylene for years of extreme abuse; the patented rod system releases the beacon when submerged in water between 4.9 and 13.1 ft (1.5-4 m)

Product Number	9435/9455
Fits	9435: Satellite 406™, GlobalFix™ (RLB-35) 9455: Satellite ₂ 406™, RapidFix™ 406
Size	17.5 x 6.25 x 4.8" (44.4 x 15.9 x 12 cm)
Weight	3 lbs (1.36 kg)



HydroFix™ Hydrostatic Release Unit for Category I EPIRB

A patented rod system does not rely on a battery, blade or pyrotechnic device to release the beacon. This advantage allows for a quick, seamless and reliable release in an emergency. Note that this is a date-stamped product and must be replaced every 2 years from the date of installation or 4 years from the date of manufacture.

- // Allows release of a beacon from a Category I bracket when submerged in water between 4.9 – 13.1 ft (1.5 – 4 m)
- // Easily replaceable
- // 100% factory tested

Product Number	9490
Fits	Open Face™, Sea Shelter™, Sea Shelter™ ₂ and Sea Shelter™ ₃ brackets
Size	2.5 x 3.4 x 2.0" (6.3 x 8.6 x 5.0 cm)
Weight	3.3 oz (93.6 g)



LowPro™₃ Category II Bracket

This low-profile bracket features an incredibly small footprint for bulkhead mounting. Made of high-density, UV-stabilized polyethylene, the LowPro™₃ will securely store your GlobalFix™ iPRO/PRO even after years of abuse.

- // One-way mounting eliminates the possibility of installing EPIRB backwards
- // Integral de-activation magnet prevents the EPIRB from transmitting until deployed
- // Two part design allows de-activation magnet to unclip from bracket for storage on the EPIRB in a ditch bag to prevent false alarms

Product Number	9502
Fits	GlobalFix™ iPRO (P/N 2848.0), GlobalFix™ PRO (P/N 2844)
Size	4.5 x 6.1 x 3.4" (12.17 x 15.34 x 8.79 cm)
Weight	5.08 oz (144 g)

LowPro™₂ Category II Bracket

Manual Category II LowPro™₂ bracket has a low profile and is easy to rail mount or secure on deck.

Product Number	9430
Fits	Satellite 406™, Satellite ₂ 406™, RapidFix™ 406, GlobalFix™ (RLB-35)
Size	5.2 x 6.9 x 2.6" (13.3 x 17.4 x 6.4 cm)
Weight	5.0 oz (141 g)

For further information please contact:

ACR Products
Cobham Life Support
5757 Ravenswood Rd.
Fort Lauderdale, Florida 33312 U.S.A.
Tel: 1-954-981-3333
Fax: 1-954-983-5087
www.acrelectronics.com